

Our versatile, in-line gas flush, heat seal machine with vacuum system provides high speed MAP capabilities and comes with interchangeable tooling and a built-in die cutter that automatically trims film to fit. Includes programmable features and technology to substantially increase the shelf life of your product and ensure packaging meets governmental standards as required.



FAST

- Automatic feed and seal feature
- Display shows number of cycles sealed in shift
- 5 minute warm up time
- Simple pocket and die change over
- Seals up to 10 cycles per minute, depending on tray size and material



VERSATILE

- Interchangeable pockets and dies
- Custom pockets and dies available
- Choice of automatic or manual seal
- Optional date printer
- Adjustable heat settings & dwell time
- Registered print capability



SAFE

- Automatic Shut Off to Prevent Injury
- All moving mechanisms are guarded, closing off potential pinch points



OUALITY

- Die cuts around container for an attractive look
- Consistent, Leak-Proof Seals
- Film tensioner provides a wrinkle-free seal
- Low maintenance
- Heavy duty, stainless steel construction
- 12 month warranty on parts
- Digital controls with microcomputer program



MAPVAC-5500

Need customer support? Call 855.454.3732

IN-LINE GAS FLUSH VACUUM HEAT SEAL MACHINE







MACHINE DIMENSIONS

40"W x 99"L x 57"H

MAX SIZE TRAY DIMENSIONS

420mm x 290mm

MAX WIDTH OF FILM

13 inches

MAX DIAMETER OF FILM ROLL

9 inches

4-UP MAX OUTPUT CAPABILITY

1-Vac & Gas Flush: 1,200 pcs/hour 2-Gas Flush Only: 2,400 pcs/hour 4-Seal Only: 2,880 pcs/hour

ELECTRICAL REQUIREMENTS

220-240 Volt, 3 Phase

NET WEIGHT

992lbs

COMPRESSED AIR REQUIREMENTS

5HP Compressor

INERT GAS REQUIREMENT


80 psig and 5 scfm

OXYGEN RESIDUAL CAPABILITY


0.5%-2% on solid product

INERT GASES


Nitrogen, Carbon Dioxide, Noble Gases







FOR TWO TRAYS



FOR FOUR TRAYS